



XTRs

Semi-automatic, two-station, rotary-table, tray sealing machine.

The successor to the GTR, the XTRs is capable of sealing 30 packs per minute with a 2 impression tool, without the need for compressed air. The all electric sealing creates a more consistent and efficient seal force with reduced energy usage and total running costs.

The user friendly design includes integrated HMI with multi-language settings, recipe driven control and automatic tool lock. Quick release tooling enables the user to switch from one tray size to another in less than 5 minutes. The machine itself is fully portable with an automatic film-feed and is available with optional 'free-flow' gas flush, Modified Atmosphere Packaging (MAP) to enable extended shelf life.

XTRs Specifications

Height	1695mm
Standard Length	1257mm
Width	1240mm
Weight	446kg
Electrical Supply	200V 16A

Features & Benefits

• Electric seal gives greater and more consistent seal force.

seal

- PLC based temperature control.
- No compressed air required. Reduces energy usage and total cost of ownership.
- Fully graphical HMI with multi-language.
- Diagnostics and alerts displayed on HMI and recorded to audit trail.
- Recipe driven product change.
- Automatic tool lock.
- Open and hygienic design for ease of maintenance and cleaning.
- Tool loading from front of machine.
- Compatible with legacy GTR tooling.
- Optional features include MAP gas flush and print coding

XTRs Sealing capacity

No. of Trays	Width	Length	Depth	Diameter
One	270mm	438mm	105mm	270mm
Two	270mm	207mm	105mm	207mm
Three	270mm	104mm	105mm	104mm
Four	270mm	71mm	105mm	71mm











POULTRY | POLYPROP

FISH | BOARD

SANDWICHES | BOARD

SOFT FRUIT | A-PET

DESSERTS | A-PET