

## X-59 Can Closer



# High Speed Seaming Technology for Liquid Applications

jbtc.com

#### A unique concept

The X-59 can closer has all machine gearing in one oil bath at the top housing of the closer. This unique concept is what sets the X-59 apart from the competition in terms of trouble-free operation, extreme reliability and low maintenance requirements.

### Sanitary design

By combining all stainless steel, highly sanitary construction with easy access to product contact areas, the X-59 closer is particularly suitable for applications requiring high standards of hygiene or where highly corrosive products are being filled. An optional Wash-In-Place (WIP) system is available.

#### Operator safety and ergonomics

Full length stainless steel guards with polycarbonate windows and optional LED lighting are an integral part of the machine. Wide, electrically and mechanically interlocked doors are designed for easy accessibility to the seaming area for maintenance, adjustments and change-over. The totally enclosed design, a reduced number of gears used and a quiet power belt drive system, all contribute to a considerable reduction in noise level.









### Fully automatic lubrication

The fully automatic oil flow system lubricates all machine parts, including seaming heads, lifter tables and seaming rolls, without stopping the machine. The system uses USDA and FDA approved food grade oils. A high performance oil recovery and filtration system is also included.

#### Ease of maintenance

Our X-59 features easy access to all major assemblies for quick maintenance, seam adjustment and removal of parts. Down-time and related production losses are kept to a minimum.

#### Consistent seam quality

Power-driven seaming spindles and lifter plates ensure consistent production of high-quality double seams, even on the lightest of light-weight cans. The X-59 is delivered with long life tooling such as: TiC coated rolls, chucks and knock-out pads.

#### Air removal


Efficient air removal from the can head-space is achieved by a proven undercover gassing system.

#### Low spillage

Stainless steel, spring-loaded knock-out pads and reduced diameter lifter tables with low lift cams minimize product spillage.

CHAIN SPACING MODEL # SEAMING HEADS SPEED (cph) (mm) 659 6 133,3 36 000 - 39 000 101.6 48 000 - 52 000 859 8 60 000 - 72 000 1059 10 111,2 or 104,7 1259 12 92,1 or 95,1 72 000 - 90 000





#### COUNT ON JBT TO HELP PROTECT YOUR INVESTMENT

JBT's greatest value in PRoCARE® services comes from preventing unexpected costs through smart, purposeful, and timely maintenance based on unmatched knowledge and expertise. PRoCARE service packages are offered as a maintenance agreement in various service levels, depending on your production and cost management requirements.



FRESH PRODUCE TECHNOLOGIES | FRESH-CUT, ROBOTICS, STEAMING | FRUIT AND VEGETABLE PROCESSING | SECONDARY PROCESSING | ASEPTIC SYSTEMS | FILLING AND CLOSING | IN-CONTAINER STERILIZING | TRAY SEALING | SECONDARY PACKAGING | HIGH-PRESSURE PROCESSING | POWDER PROCESSING | TUNA PROCESSING















**FranRica**<sup>®</sup>





**PRoCARE** 

North America

John Bean Technologies Corporation 2300 Industrial Avenue Madera CA 93639 USA Phone: +1 559 661 3200 Fax: +1 559 661 3156

Latin America

JBT de México S de RL de CV Camino Real a San Andrés Cholula No. 2612 Col. San Bernardino Tlaxcalancingo 72820 San Andrés Cholula, Puebla México Phone: +52 222 329 4902 Fax: +52 222 329 4903

South America

John Bean Technologies Máq. e Equip. Ind. Ltda. Av. Eng Camilo Dinucci 4605 14808-900 Araraquara, São Paulo Brazil Phone: +55 16 3301 2000 Fax: +55 16 3301 2144

Europe John Bean Technologies NV Breedstraat 3

9100 Sint-Niklaas Belgium Phone: +32 3 780 1211 Fax: +32 3 777 7955

#### Asia Pacific

John Bean Technologies (Thailand) Ltd. No. 2525 FYI Center Building 2, 9th Floor Unit No. 2/901-2/903, Rama IV Road Klongtoei, Bangkok 10110 Thailand Phone: +66 (0) 2257 4000 infoasia-jbtfoodtech@jbtc.com

South Africa John Bean Technologies (Pty) Ltd. Koper Street Brackenfell Cape Town, South Africa 7560 Phone: +27 21 982 1130 Fax: +27 21 982 1136



## We're with you, right down the line.™

hello@jbtc.com | jbtc.com

